

N 9 2 - 2 2 0 2 0

ADVANCED TRACKING AND DATA RELAY SATELLITE SYSTEM


Daniel Stern
NASA Headquarters
Washington, D.C. 20546

ADVANCED TDRSS

PURPOSE:

- Provide NASA needs for satellite tracking and communications through the year 2012
- Maintain and augment the current TDRS System when available satellite resources are expended in the latter part of the next decade
- Provide the necessary ground upgrade to support the augmented services
- Introduce new technology to reduce system life-cycle cost.

ATDRSS Configuration



TDRS LAUNCH SCHEDULE

TDRS 1 - Launched 4/83; Degraded Capability

TDRS 2 - Lost in Challenger accident 1/86

TDRS 3 - Launched 9/88

TDRS 4 - Launched 3/89; replaced F-1

TDRS 5 - In orbit spare in 1990

TDRS 6 - Ground spare or fourth satellite in constellation

TDRS 7 - Replacement spacecraft; available 1992


TDRS 8 - Optional spacecraft; not available before 1994

ATDRS - Advanced TDRS; not available before July 1997


ADVANCED TDRSS STATUS

- Completed 18-month Conceptual Design Studies (Phase A) in March; Ford, GE, Hughes, Lockheed, TRW
- Phase B RFP to be released in August 1989 for a competitive award to multiple contractors
- Delivery of the first ATDRS is planned for July, 1997

ATDRSS PROGRAM SCHEDULE



TDRSS EVOLUTION



POTENTIAL SERVICES UNDER EVALUATION

| | <u>Status</u> |
|--|---------------|
| • Cost vs. benefit of closing the zone of exclusion | Defer |
| • Increased single access capacity (>300 Mb/sec) | ✓ |
| • Direct downlink to some locations or users | Defer |
| • Demand Access on MA channels | Study |
| • Interoperability with other data relay satellite systems | Defer |
| • Increased satellite reliability and redundancy | ✓ |
| • GEO user coverage | ✓ |
| • Command/Navigation Broadcast (Beacon) | Study |
| • Pre-Operational Demonstration (Satellite Expansion) | ✓ |

TDRSS / ATDRSS BASELINE SERVICE COMPARISON

| Single Access | Max. Rate (MBPS) | No. of Channels | |
|---|---------------------------|--------------------|---------------------|
| | | 1996 TDRSS Cluster | 2003 Advanced TDRSS |
| S-Band | FWD.....0.3 RTN.....6 | 8 | 4* + Spare |
| Ku-Band | FWD.....25 RTN.....300 | 8 | 4* + Spare |
| Ka-Band | FWD.....50 RTN.....650 | | 4* + Spare |
| Total No. of Independent Pointable Antennas | | 8 | 8 + 2 Spare |

| | TDRSS | ATDRSS |
|------------------------|---|---------------------------------------|
| Multiple Access | FWD.....4 @ 10 KBPS RTN.....20 @ 50 KBPS | 8 @ 10 KBPS (+3 dBW) 12 @ 3 MBPS** |

| | TDRSS | ATDRSS |
|-------------------|-------------------|--------------------------------------|
| Tracking Accuracy | 150 M, 3 σ | Study Improvement to 50M, 3 σ |

* Minimum- possibly larger ** MA Gain equal to TDRS Single Access - S-Band

QPSK

- Expansion to Ka-Band obviates need for highly bandwidth-efficient modulation techniques
- Minimizes User and Spacecraft impact

ATDRSS MODULATIONS

Telecommand:

SQPN and data

- PN Range and Command Channel
PN Spread for ≤ 300 KBPS
- New 50 MBPS Ka-Band is
Balanced SQPSK

Telemetry:

- DG1, mode 1+2

SQPN and data

- PN Spread at Lower Rates

- DG1, mode 3

PSK in quadrature

- Only I-Channel is PN Spread

- DG2

BPSK, QPSK, SQPSK

- Unbalanced and Balanced Mode
- SQPSK Used for Equal
I & Q Data Rates

ATDRSS SIGNAL PARAMETERS

- Bent-Pipe as TDRS
- 1×10^{-5} BER
- Convolutional Encoding/Viterbi Decoding
at 1/2 & 1/3 rates for some modes as in TDRS
 - User can provide own End-to-End Encoding

CONCLUSIONS

- **No ATDRS Spacecraft Requirement for New Modulation Techniques**
- **Data Rate of 650 MBps is Required**
 - **Opportunities Exist for Applications of Advanced Modulation Techniques for Ground Data Distribution**
- **Space Station Freedom Requirement for 650 MBps Data Some Time After the Year 2000**

